

# UNITED WUBLLI POWER ANYWHERE Lucas The improved

Do you have to work in remote and hard-to-reach places? The improved PST.2500/3 Power Station is the perfect solution when it comes to mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of mobility. With a continuous load of 3,500 Watt and a peak load of 3,500 Watt and 3,500 Watt and

### BENEFITS OF THE PST.2500/3

- Continuous load of 3,500 W
- Peak load of 7,000 W
- High Capacity Ternary Lithium Ion Cells
- Fast rechargeable (3 hours)
- 3 power outlets 220 V
- Electricity supply without fluctuations
- Can be used practically everywhere
- Easy to use
- Ideal for heavy duty industrial power tools
- No noise, no smell, no pollution





CHARGED

**HOURS** 

## **PST.2500/3**

#### **Power Station**

## **EUROBOOR**

#### **Technical data**

Output voltage	AC 220 V 50/60 Hz
Socket specification	3 x EU type F (grounded) IP44
Rated output power	Max. 3,500 W
Surge power Max.	Max. 7,000 W
Overload protection	Fuse (20 A)
Battery capacity	2.496 KWh
Battery type	Ternary Lithium Ion battery cell
Battery voltage	DC 48 V
Battery cooling	Air (2 x automatic air fans)
Charger voltage	AC 200-240 V 50/60 Hz
Charger output	54.6 V (15 A)
Charging time	± 3.0 hours
Charging cycles	1,500 x (capacity > 80%)
Operating temperature	-20°C up to 40°C
Charging temperature	0°C up to 30°C
Storage temperature	0°C up to 25°C
Dimensions (L x W x H)	550 x 310 x 460 mm
Weight	28.3 kg
Ingress protection class	IP21S (indoor)





Euroboor makes every effort to meet quality and integrity requirements. That is why we as an organization are proud of the recognition of some leading organizations worldwide:













