

## Data Sheet

**Type Number** ..... 20317  
**Designation IEC** ..... SR 516 SW  
**System** ..... Silver oxide / Zinc / NaOH



**Nominal Voltage** ..... 1,55 V  
**Typical Capacity C** ..... 10,5 mAh  
 Load 68 kOhm, at 20°C down to 1.2 V

**Weight (approx.)** ..... 0,18 g  
**Volume** ..... 0,04 ccm  
**Coding** ..... Date of Manufacturing  
 Month / Year

|                           |       |      |
|---------------------------|-------|------|
| <b>Temperature Ranges</b> | min   | max. |
| Storage .....             | -10°C | 60°C |
| Discharge .....           | -10°C | 60°C |

|                    |      |      |
|--------------------|------|------|
| <b>Dimensions</b>  | min  | max. |
| Diameter (Ø).....  | 5,65 | 5,8  |
| Height (A/B) ..... | 1,47 | 1,65 |

**Segment** ..... Watch

**Main Applications** ..... Watch  
 Electronic

**Typical Capacities (at 20°C)**

| Discharge Type            | Load     | End Voltage: | 1.2 V |
|---------------------------|----------|--------------|-------|
| Continuous<br>24h/d, 7d/w | 121000 Ω | Time:        | 412 h |