

## Data Sheet

**Type Number** ..... 20391  
**Designation IEC** ..... SR 55  
**System** ..... Silver oxide / Zinc /  
 KOH - Electrolyte



**Nominal Voltage** ..... 1,55 V  
**Typical Capacity C** ..... 42 mAh  
 Load 13 kOhm, at 20°C down to 1.2 V

**Weight (approx.)** ..... 0,9 g  
**Volume** ..... 0,18 ccm  
**Coding**..... Date of Manufacturing  
 Month/Year

**Temperature Ranges**

|                 |       |      |
|-----------------|-------|------|
|                 | min   | max. |
| Storage .....   | -10°C | 65°C |
| Discharge ..... | -10°C | 65°C |

**Dimensions**

|                    |       |      |
|--------------------|-------|------|
|                    | min   | max. |
| Diameter (Ø) ..... | 11,25 | 11,6 |
| Height (A/B) ..... | 1,85  | 2,1  |

**Segment** ..... Watch / High Drain

**Main Applications** ..... Watch  
 Photo  
 Electronic

**Typical Capacities (at 20°C)**

| Discharge Type                            | Load    | End Voltage:    | 1.2 V |
|---|---------|-----------------|-------|
| Continuous<br>24h/d,7d/w<br>Current [µA]: | 13000 Ω | Time:           | 340 h |
|   |         | Capacity [mAh]: | 42    |
|   | 120     | Energy [mWh]:   | 65    |